

A COMPREHENSIVE RANGE with OPTIMISED comfort!

Ergonomic models

Perfectly designed for all hand types. Soft, flexible and strong, they allow great dexterity.

Clear, durable marking with colour per class

color according to the class (max voltage level).



Bi-colour gloves

on class 1/2/3/4 allows to quickly detect any abrasion, cut or other mechanical surface damage that could alter the dielectric properties of the glove.



Flashcode

Traceability provides access to read the gloves' test reports.



Wide range of sizes

from 7 to 12 covering all needs (male/female).



Rolled cuff

For greater comfort and ease of use.



ACCESSORIES

Overgloves
Ref. : CG-981-(*)



Pneumatic glove tester
Ref. : CG-117



Overgloves
Ref. : CG-991-(*)



Gloves box
Ref. : CG-35/2



Undergloves
Ref. : CG-80-(*)



* Size 8 to 12.



10/20 Avenue Jean-Jaurès
B.P.2 - 92222 BAGNEUX Cedex
(France)
Phone: + 33 1 42 31 46 00
Fax: + 33 1 42 31 46 32
www.catuelec.com

CATUTM

SICAME GROUP

IEC 60903
ASTM D 120

Electrical insulating rubber GLOVES

NEW

DEXTERI ⁺
RANGE

- ERGONOMIC SHAPE
- SIZE : 7 TO 12
- BI-COLOUR
- CLEAR & SMART MARKING
- ROLLED CUFF
- TRACEABILITY



CATUTM

SICAME GROUP



New range DEXTERI+

CATU electric insulating gloves provide effective individual protection for anyone required to work on live voltages or perform operations on or in proximity to electric installations. The mechanical strength models have, in addition to electric shock protection, protection against abrasion, perforation and other mechanical damage.



CATU has worked with the main players in the transport and distribution of electric energy in France and worldwide. CATU has now become one of the global leaders in the market for the prevention of electric hazards. CATU is a subsidiary of the SICAME GROUP, specialised in electric energy business activities (www.sicame.com).

NATIONAL AND INTERNATIONAL REPUTATION

CATU invest significant resources into developing and producing comprehensive ranges of innovative products for professionals in the electricity sector in more than 100 countries.

COMPLETE PRODUCTION DEDICATED TO MANUFACTURING INSULATING GLOVES
CATU has integrated the design and manufacture of electric insulating gloves into one of its production units.

CATU controls a unique manufacturing procedure on the market and has a patented process.

This technological innovation has given the company control and expertise in all its ranges of insulating gloves to meet the requirements of the standards and the constraints of its customers.



ELECTRIC INSULATING GLOVES

Compliant with the IEC 60903/EN 60903 standard

Packaging in coloured plastic bags to identify the class.

Reference	Class	Voltage	Thickness (mm)	Category	Length (mm)	Color
CG-05-(*)	00	≤ 500V	1.0	AZC	360	Natural
CG-10-(*)	0	≤ 1 000V	1.31	AZC	360	
CG-1-(**)	1	≤ 7 500V	1.95	AZC	360	Bi-colour : red outside, natural inside.
CG-2-(**)	2	≤ 17 000V	2.64	RC	360	
CG-3-(**)	3	≤ 26 500V	3.45	RC	360	
CG-4-(**)	4	≤ 36 000V	3.65	RC	410	

(*) complete by size codes A=8, B=9, C=10, D=11.

(**) complete by size codes 7 to 12 (sizes 7 and 12 on request).



ELECTRIC INSULATING GLOVES

MECHANICAL STRENGTH MODEL


Compliant with the IEC 60903/EN 60903 standard

Packaging in coloured plastic bags.

Reference	Class	Voltage	Thickness (mm)	Category	Length (mm)	Color
CGM-00-(*)	00	≤ 500V	1.8	RC	360	Bi-colour : orange outside, natural inside.
CGM-0-(*)	0	≤ 1 000V	1.94	RC	360	
CGM-1-(*)	1	≤ 7 500V	2.8	RC	360	
CGM-2-(*)	2	≤ 17 000V	3.3	RC	360	
CGM-3-(*)	3	≤ 26 500V	3.6	RC	360	
CGM-4-(*)	4	≤ 36 000V	4.2	RC	410	

(*) complete by size codes 7 to 12 (sizes 7 and 12 on request).

** Tested to arc flash standard IEC 61482-1-2 class 2.



ASTM INSULATING RUBBER GLOVES

Compliant with the ASTM D 120 standard

Reference	Class	Voltage	Thickness (mm)	Category	Length (inches)	Color
CGA-00-(*)-B	00	≤ 500V	0.75	I	14	Black
CGA-0-(*)-B	0	≤ 1 000V	1.02	I	14	
CGA-1-(*)-NB	1	≤ 7 500V	1.52	I	14	Bi-colour : black outside, natural inside.
CGA-2-(*)-NB	2	≤ 17 000V	2.29	I	14	
CGA-3-(*)-NB	3	≤ 26 500V	2.92	I	14	
CGA-4-(*)-NB	4	≤ 36 000V	3.56	I	16	

(*) complete by size codes 7 to 12 (sizes 7 and 12 on request).